


ULTRADYN PRODUCTS SPECIFICATION

- HOLLOW FIBER UF MEMBRANE MODULE -

FS10-FS-FUY03A1



Module	A	B	C	D	E	F
Dimension mm	1,129	985	72	130	89	100

Module components			
Article	Name	Material	Num.
①	Nozzle cap	Polysulfone	2
②	Cap	Polysulfone	2
③	Case	Polysulfone	1
④	O-Ring type WG-21	FPM	2
-	Potting resin	Epoxy resin	-

FPM: Fluoro rubber

Standard configurations

Filtration type	Ultrafiltration		
Membrane material	Polyacrylonitrile		
Molecular cutoff	30,000	Dalton	
Hollow fiber inner diameter	1.0	mm	
Membrane area	4.2	m ²	
Standard water flux ⁽¹⁾	1.3	m ³ /h	
Shipping water flux range ⁽¹⁾	0.9	m ³ /h	
Feed inlet pressure, max. ⁽³⁾	0.6	MPa	
Transmembrane pressure, max.	0.3	MPa	
Temperature, max.	45	°C	
Applicable pH range	2 ~ 11		
Standard inlet feed flow ⁽²⁾	3.8	m ³ /h	
Weight at operation	8.5	kg	
Weight at shipping	2.5	kg	
Standard preservative	1000 ppm Benzoic acid		
Connectors	Feed/Conc.:	2S Ferrule	
	Permeate:	1S Ferrule	

⁽¹⁾ Initial water flux by dead end filtration with pure water under T.M.P. 0.1 MPa at 25°C

⁽²⁾ Standard condition is adjusted to 1 m/sec feed velocity. Please notice that the optimum velocity is different for each application.

⁽³⁾ This value is for room temperature.

Note: Applicable max. pressure depends on operating temperature. Ensure instruction manual.

DAICEN Membrane Systems Ltd. is the manufacturer of the ULTRADYN modules and markets and distributes them under the registered trademark MOLSEP®.

MICRODYN-NADIR behält sich das Recht vor, Angaben ohne vorherige Ankündigung anzupassen.
We reserve the right to change specifications without prior notification.

MICRODYN-NADIR GmbH
Industriepark Kalle-Albert
Kasteler Straße 45
D-65203 Wiesbaden

Telefon: +49 (0) 611/962-6001
Telefax: +49 (0) 611/962-9237
E-Mail: info@microdyn-nadir.de
Internet: www.microdyn-nadir.de

