



# TRISEP® DS Food & Dairy

## NP010 Series

TRISEP sanitary membrane elements for food & dairy applications have a long history of outstanding, stable field performance. NADIR® NP010 polyethersulfone (PES) membrane exhibits nanofiltration properties and a molecular weight cut-off in the range of 1,000 – 1,200 Da after a high-pressure stabilization, offering unique separation properties for process applications. TRISEP elements are available with a number of different feed spacers and in all sizes common in the industry. TRISEP DS elements are built with FDA compliant materials, are compliant with European food regulations (EU 10/2011 and EC 1935/2004) and comply with USDA standards.

### Membrane Characteristics

Membrane	Nominal M.W.C.O. (Da)	Na <sub>2</sub> SO <sub>4</sub> Salt Rejection (%) <sup>a</sup>
NADIR® NP010	1,000 – 1,200	35 – 75

Maximum Operating Pressure.....	40 bar (580 psi)
Maximum Operating Temperature.....	50°C (122°F)
Cleaning pH Range <sup>1</sup> .....	1.0 – 12.0
Cleaning Chlorine Tolerance .....	200 ppm for sanitization at pH ≥ 10.5
Maximum Pressure Drop .....	1 bar (15 psi) per element 4 bar (60 psi) per housing

<sup>1</sup> Refer to temperature and pH limits in *Membrane Cleaning Guide – Food & Dairy: UF & MF Elements (TSG-C-004)*.

### Design Information

MICRODYN-NADIR has the versatility to customize elements to meet customers' specific needs. Please contact MICRODYN-NADIR for information on customized solutions.

Model	Membrane Area m <sup>2</sup> (ft <sup>2</sup> )	Feed Spacer Thickness (mil) <sup>b</sup>
TRISEP® DS NP010 3838B	7.0 (75)	31
TRISEP® DS NP010 3838C	5.7 (61)	46
TRISEP® DS NP010 6338B	20.5 (221)	31
TRISEP® DS NP010 6338C	17.1 (184)	46
TRISEP® DS NP010 6338F	11.5 (124)	80
TRISEP® DS NP010 8038B	32.0 (344)	31
TRISEP® DS NP010 8038C	25.0 (269)	46
TRISEP® DS NP010 8038F	18.0 (194)	80

<sup>a</sup> Test conditions: 5,000 ppm Na<sub>2</sub>SO<sub>4</sub>, 40 bar (580 psi), 20°C (68°F). Membrane specifications may change without notice as design revisions occur.  
<sup>b</sup> All models on this sheet are net wrapped and have diamond shaped feed spacers.




## Product Specification (continued)

### Physical Dimensions

Model	Element Weight kg (lbs) <sup>c</sup>	Dimensions, mm (inches)			Permeate Tube
		A	B	C <sup>d</sup>	
TRISEP® DS NP010 3838B	4 (9)	965 (38.0)	96 (3.8)	21.1 (0.83)	Female
TRISEP® DS NP010 3838C	4 (9)	965 (38.0)	96 (3.8)	21.1 (0.83)	Female
TRISEP® DS NP010 6338B	11 (24)	965 (38.0)	162 (6.3)	28.9 (1.138)	Female
TRISEP® DS NP010 6338C	11 (24)	965 (38.0)	162 (6.3)	28.9 (1.138)	Female
TRISEP® DS NP010 6338F	11 (24)	965 (38.0)	162 (6.3)	28.9 (1.138)	Female
TRISEP® DS NP010 8038B	16 (36)	965 (38.0)	201 (7.9)	28.9 (1.138)	Female
TRISEP® DS NP010 8038C	16 (36)	965 (38.0)	201 (7.9)	28.9 (1.138)	Female
TRISEP® DS NP010 8038F	16 (36)	965 (38.0)	201 (7.9)	28.9 (1.138)	Female

<sup>c</sup> Shipping weight is dependent on packaging material and quantity shipped.  
<sup>d</sup> Dimension "C" is the Inner Diameter.



### Important Information

- Start-up:** MICRODYN-NADIR recommends flushing elements for 30 minutes at low pressure and discarding permeate during the flush prior to operation. For a more detailed start-up procedure, please see *Element Start-Up Guide – System Start-Up* (TSG-O-005).
- Cleaning:** TRISEP® membrane elements must be cleaned periodically to ensure proper operation and to prevent membrane damage. Please see *Membrane Cleaning Guide – Food & Dairy: UF & MF Elements* (TSG-C-004).
- Storage:** TRISEP membrane elements must be stored appropriately to ensure proper operation and to prevent membrane damage. Please see *Element Storage Guides* (TSG-O-009 & TSG-O-010).

### Customizable Specialty Elements

MICRODYN-NADIR offers a full range of membranes and element designs for challenging water and process applications. Technologies include low-fouling RO, submerged UF, continuous high temperature, ultra-high pressure, unique sanitary designs and more. Contact MICRODYN-NADIR to customize a product that satisfies your specific requirements.

## Solving Unmet Needs with Customized Products



Headquarters  
 MICRODYN-NADIR GmbH  
 Building D512  
 Kasteler Straße 45  
 65203 Wiesbaden  
 Germany  
 info@microdyn-nadir.de  
 www.microdyn-nadir.de

USA Office  
 MICRODYN-NADIR US, Inc.  
 93 South La Patera Lane  
 Goleta, CA 93117  
 USA  
 info@microdyn-nadir.com  
 www.microdyn-nadir.com/en  
 www.microdyn-nadir.com/trisep

China Office  
 MICRODYN-NADIR (Xiamen) Co. Ltd.  
 No. 66 Jinting North Road Xinglin  
 Xiamen, China 361022  
 infochina@microdyn-nadir.com

Singapore Office  
 MICRODYN-NADIR Singapore Pte. Ltd.  
 18 Tuas Avenue 8  
 Singapore 639233  
 info@microdyn-nadir.com