



TRISEP® DS Food & Dairy

UP005 Series

TRISEP sanitary membrane elements for food & dairy applications have a long history of outstanding, stable field performance. NADIR® UP005 polyethersulfone (PES) membrane with a nominal 5,000 Da molecular weight cut-off offers the highest protein rejection in the industry for membranes with this cut-off. In field studies UP005 membrane had as much as 75% less protein passage than competitive membranes. TRISEP elements are available with a number of different feed spacers and in all sizes common in the industry. TRISEP DS elements are built with FDA compliant materials, are compliant with European food regulations (EU 10/2011 and EC 1935/2004) and comply with USDA standards.

Membrane Characteristics

Membrane	Nominal M.W.C.O. (Da)
NADIR® UP005	5,000

Maximum Operating Pressure.....	10 bar (145 psi)
Maximum Operating Temperature.....	50°C (122°F)
Cleaning pH Range ¹	1.0 – 12.0
Cleaning Chlorine Tolerance	200 ppm for sanitization at pH ≥ 10.5
Maximum Pressure Drop	1 bar (15 psi) per element 4 bar (60 psi) per housing

¹ Refer to temperature and pH limits in *Membrane Cleaning Guide – Food & Dairy: UF & MF Elements (TSG-C-004)*.

Design Information

MICRODYN-NADIR has the versatility to customize elements to meet customers' specific needs. Please contact MICRODYN-NADIR for information on customized solutions.

Model	Membrane Area m ² (ft ²)	Feed Spacer Thickness (mil) ^a
TRISEP® DS UP005 3838B	7.0 (75)	31
TRISEP® DS UP005 3838C	5.7 (61)	46
TRISEP® DS UP005 3838E	4.5 (48)	65
TRISEP® DS UP005 3838F	4.0 (43)	80
TRISEP® DS UP005 6338B	20.5 (221)	31
TRISEP® DS UP005 6338C	17.1 (184)	46
TRISEP® DS UP005 6338E	12.9 (139)	65
TRISEP® DS UP005 6338F	11.5 (124)	80
TRISEP® DS UP005 8038B	32.0 (344)	31
TRISEP® DS UP005 8038C	25.0 (269)	46
TRISEP® DS UP005 8038E	21.0 (226)	65
TRISEP® DS UP005 8038F	18.0 (194)	80
TRISEP® DS UP005 8338B	34.0 (366)	31
TRISEP® DS UP005 8338C	27.5 (296)	46
TRISEP® DS UP005 8338F	21.2 (228)	80

^a All models on this sheet are net wrapped and have diamond shaped feed spacers.




Product Specification (continued)

Physical Dimensions

Model	Element Weight kg (lbs) ^b	Dimensions, mm (inches)			Permeate Tube
		A	B	C ^c	
TRISEP® DS UP005 3838B	4 (9)	965 (38.0)	96 (3.8)	21.1 (0.83)	Female
TRISEP® DS UP005 3838C	4 (9)	965 (38.0)	96 (3.8)	21.1 (0.83)	Female
TRISEP® DS UP005 3838E	4 (9)	965 (38.0)	96 (3.8)	21.1 (0.83)	Female
TRISEP® DS UP005 3838F	4 (9)	965 (38.0)	96 (3.8)	21.1 (0.83)	Female
TRISEP® DS UP005 6338B	11 (24)	965 (38.0)	162 (6.3)	28.9 (1.138)	Female
TRISEP® DS UP005 6338C	11 (24)	965 (38.0)	162 (6.3)	28.9 (1.138)	Female
TRISEP® DS UP005 6338E	11 (24)	965 (38.0)	162 (6.3)	28.9 (1.138)	Female
TRISEP® DS UP005 6338F	11 (24)	965 (38.0)	162 (6.3)	28.9 (1.138)	Female
TRISEP® DS UP005 8038B	16 (36)	965 (38.0)	201 (7.9)	28.9 (1.138)	Female
TRISEP® DS UP005 8038C	16 (36)	965 (38.0)	201 (7.9)	28.9 (1.138)	Female
TRISEP® DS UP005 8038E	16 (36)	965 (38.0)	201 (7.9)	28.9 (1.138)	Female
TRISEP® DS UP005 8038F	16 (36)	965 (38.0)	201 (7.9)	28.9 (1.138)	Female
TRISEP® DS UP005 8338B	18 (40)	965 (38.0)	211 (8.3)	28.9 (1.138)	Female
TRISEP® DS UP005 8338C	18 (40)	965 (38.0)	211 (8.3)	28.9 (1.138)	Female
TRISEP® DS UP005 8338F	18 (40)	965 (38.0)	211 (8.3)	28.9 (1.138)	Female

^b Shipping weight is dependent on packaging material and quantity shipped.
^c Dimension "C" is the Inner Diameter.



Important Information

- Start-up:** MICRODYN-NADIR recommends flushing elements for 30 minutes at low pressure and discarding permeate during the flush prior to operation. For a more detailed start-up procedure, please see *Element Start-Up Guide – System Start-Up (TSG-O-005)*.
- Cleaning:** TRISEP® membrane elements must be cleaned periodically to ensure proper operation and to prevent membrane damage. Please see *Membrane Cleaning Guide – Food & Dairy: UF & MF Elements (TSG-C-004)*.
- Storage:** TRISEP membrane elements must be stored appropriately to ensure proper operation and to prevent membrane damage. Please see *Element Storage Guides (TSG-O-009 & TSG-O-010)*.

Customizable Specialty Elements

MICRODYN-NADIR offers a full range of membranes and element designs for challenging water and process applications. Technologies include low-fouling RO, submerged UF, continuous high temperature, ultra-high pressure, unique sanitary designs and more. Contact MICRODYN-NADIR to customize a product that satisfies your specific requirements.

Solving Unmet Needs with Customized Products



Headquarters
 MICRODYN-NADIR GmbH
 Building D512
 Kasteler Straße 45
 65203 Wiesbaden
 Germany
 info@microdyn-nadir.de
 www.microdyn-nadir.de

USA Office
 MICRODYN-NADIR US, Inc.
 93 South La Patera Lane
 Goleta, CA 93117
 USA
 info@microdyn-nadir.com
 www.microdyn-nadir.com/en
 www.microdyn-nadir.com/trisep

China Office
 MICRODYN-NADIR (Xiamen) Co. Ltd.
 No. 66 Jinting North Road Xinglin
 Xiamen, China 361022
 infochina@microdyn-nadir.com

Singapore Office
 MICRODYN-NADIR Singapore Pte. Ltd.
 18 Tuas Avenue 8
 Singapore 639233
 info@microdyn-nadir.com