

# ULTRADYN™ FE10-FC-FUC1582

## Ultrafiltration Modules


High mechanical strength, backwashable membrane in a wide range of membrane types make ULTRADYN™ hollow fiber modules suitable for all applications requiring a high level of purification and high packing density. ULTRADYN modules are available with polyethersulfone (PES), polyacrylonitrile (PAN) and cellulose tri-acetate (CTA) hollow fiber membrane types and in configurations that can be sterilized with hot water up to 98 °C, eliminating bacterial growth and preventing fouling.

ULTRADYN modules are available with a hollow fiber inner diameter range from 0.5 to 1.4 mm, and module size range from 0.1 m<sup>2</sup> to 17 m<sup>2</sup>. ULTRADYN hollow fiber modules have proven particularly successful in applications such as pure water filtration, pharmaceuticals, electronics, and surface water treatment.

### MEMBRANE CHARACTERISTICS

Membrane Chemistry	Cellulose Acetate (CTA)
Molecular Weight Cut-Off	150,000 Dalton
Hollow Fiber Inner Diameter	0.8 mm

### PHYSICAL DIMENSIONS



	A	B	C	D	E	F
Dimension – mm (inches)	1,126 (45.5)	985 (38.8)	70.5 (2.7)	130 (5.1)	89 (3.5)	85 (3.3)

Item	Description	Material	Quantity
1	Nozzle cap	Polysulfone	2
2	Cap	Polysulfone	2
3	Case	Polysulfone	1
4	O-Ring type WG-21	Fluoro-rubber (FPM)	2
-	Potting Resin	Epoxy Resin	-

ACCESSORIES

Item	Description	Material	Quantity
1	Feed/Conc. port joints	Polyvinyl chloride (PVC), TS 40	2
2	Permeate port joints	Polyvinyl chloride (PVC), TS 25	2
3	O-Ring type G-95	Fluoro-rubber (FPM)	2
-	For V-band fitting		-

OPERATING PARAMETERS & MODULE SPECIFICATIONS

Membrane Area	5.0 m <sup>2</sup> (53.8 ft <sup>2</sup> )
Standard Water Flux <sup>a</sup>	3.0 m <sup>3</sup> /h (13.2 gpm)
Shipping Water Flux <sup>a</sup>	2.1 m <sup>3</sup> /h (9.24 gpm)
Maximum Feed Inlet Pressure <sup>b</sup>	6 bar (87 psi)
Maximum Transmembrane Pressure	2 bar (29 psi)
Maximum Temperature	40°C (104°F)
Applicable pH range	4 ~ 8
Standard Inlet Feed Flow <sup>c</sup>	3.8 m <sup>3</sup> /h (16.7 gpm)
Operating Weight	9.0 kg (19.8 lb)
Shipping Weight	3.0 kg (6.6 lb)
Standard Preservative	2% Formalin
Feed/Conc. Connectors	V band coupling
Permeate Connectors	25 A

a Initial water flux by dead end filtration with pure water under TMP 0.1 MPa at 25°C.

b Standard condition is adjusted to 1 m/sec feed velocity. The optimum velocity is different for each application.

c This value is applicable at 25°C.

d Maximum pressures depend on operating temperature. See instruction manual for further information.

\* DAICEN Membrane Systems Ltd. is the manufacturer of the ULTRADYN modules and markets and distributes them under the registered trademark MOLSEP®.

CUSTOMIZABLE SPECIALTY ELEMENTS

MICRODYN-NADIR offers a full range of membranes and element designs for challenging water and process applications. Technologies include low-fouling RO, submerged UF, continuous high temperature, ultra-high pressure, unique sanitary designs and more. Contact MICRODYN-NADIR to customize a product that satisfies your specific requirements.

## Contact

**Europe**

Germany: +49 611 962 6001

Italy: +39 0721 1796201

info@microdyn-nadir.com

**America**

USA: +1 805 964 8003

Brazil: +55 11 3378 7500

info@microdyn-nadir.com

**Asia**

China: +86 592 677 5500

Singapore: +65 6457 7533

infochina@microdyn-nadir.cn