

# ULTRADYN™ FN20-VP-FUS1582

## Ultrafiltration Modules


High mechanical strength, backwashable membrane in a wide range of membrane types make ULTRADYN™ hollow fiber modules suitable for all applications requiring a high level of purification and high packing density. ULTRADYN modules are available with polyethersulfone (PES), polyacrylonitrile (PAN) and cellulose tri-acetate (CTA) hollow fiber membrane types and in configurations that can be sterilized with hot water up to 98 °C, eliminating bacterial growth and preventing fouling.

ULTRADYN modules are available with a hollow fiber inner diameter range from 0.5 to 1.4 mm, and module size range from 0.1 m<sup>2</sup> to 17 m<sup>2</sup>. ULTRADYN hollow fiber modules have proven particularly successful in applications such as wine filtration, pure water filtration, pharmaceuticals, electronics, and surface water treatment.

### MEMBRANE CHARACTERISTICS

<b>Membrane Chemistry</b>	Polyethersulfone (PES)
<b>Molecular Weight Cut-Off</b>	150,000 Dalton
<b>Hollow Fiber Inner Diameter</b>	0.8 mm

### PHYSICAL DIMENSIONS



Item	Description	Material	Quantity
1	Hollow Fiber	Polyethersulfone	-
2	Potting Resin	Polyurethane	-
3	Inner Net	Nylon	1
4	Cartridge Case	Polyvinyl chloride	1
5	O-Ring type WG-36	Ethylene Propylene Rubber (EPM)	4

**OPERATING PARAMETERS & MODULE SPECIFICATIONS**

<b>Membrane Area</b>	16.0 m <sup>2</sup> (172 ft <sup>2</sup> )
<b>Standard Water Flux<sup>a</sup></b>	27.5 m <sup>3</sup> /h (121 gpm)
<b>Shipping Water Flux<sup>a</sup></b>	18 m <sup>3</sup> /h (79 gpm)
<b>Maximum Transmembrane Pressure</b>	3 bar (44 psi)
<b>Maximum Temperature</b>	40°C (104°F)
<b>Applicable pH range</b>	2 - 12
<b>Standard Inlet Feed Flow<sup>c</sup></b>	13.3 m <sup>3</sup> /h (58 gpm)
<b>Operating Weight</b>	23 kg (50.7 lb)
<b>Shipping Weight</b>	16 kg (35 lb)
<b>Standard Preservative</b>	0.3 % w/v Glycakil

a Initial water flux by dead end filtration with pure water under TMP 0.1 MPa at 25°C.

b Standard condition is adjusted to 1 m/sec feed velocity. The optimum velocity is different for each application.

c This value is applicable at 25°C.

d Maximum pressures depend on operating temperature. See instruction manual for further information.

\* DAICEN Membrane Systems Ltd. is the manufacturer of the ULTRADYN modules and markets and distributes them under the registered trademark MOLSEP®.

**CUSTOMIZABLE SPECIALTY ELEMENTS**

MANN+HUMMEL Water & Fluid Solutions offers a full range of membranes and element designs for challenging water and process applications. Technologies include low-fouling RO, submerged UF, continuous high temperature, ultra-high pressure, unique sanitary designs and more. Contact us to customize a product that satisfies your specific requirements.

Contact

**Europe**

Germany: +49 611 962 6001  
 Italy: +39 0721 1796201  
 info@microdyn-nadir.com

**Americas**

USA: +1 805 964 8003  
 sales.mnus@microdyn-nadir.com

**Asia**

Singapore: +65 6457 7533  
 China: +86 10 8413 9860  
 waterchina@mann-hummel.com